

MATTE

Specialty Materials™

THE BEST GARMENT DECORATION PRODUCTS

ThermoFlex **TURBO**

- Turbo adhesive allows a low temperature and quick press time, which eliminates press marks
- Durable, weeds easily, and has a soft hand and strong grip
- Does not encourage dye-migration since it has a low heat and quick press time
- Pressure-sensitive carrier enables easy weeding and repositioning

Acceptable Fabrics

Cotton, Uncoated Polyester, Fabric Blends, Spandex, Lycra, Wool, Linen, and Nylon (See Pressing Instructions below for Nylon)

Sizing Available

Available Widths (in.): 15" and 20"
Available Lengths (ft.): 15', 30', 45', 60', 90', and 150' rolls





Thickness



4 mils/100 microns


Special Precautions


★Columbia Blue, Metallics, and Neons cannot be layered beneath anything.

Application Instructions for Cotton, Polyester, & Cotton/Polyester Blends

 45° Blade Recommended
  Cut this material in mirror image
  270°F
  Medium, even pressure

 Press for 5 Seconds
  PEEL Peel warm


 Machine wash using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not iron directly onto this material. Wash temperature should not exceed 140°F.





CPSIA
COMPLIANT





Application Instructions for Nylon


 45° Blade Recommended


 Cut this material in mirror image

 300°F

 Low, even pressure

 Pre-press garment for 5 seconds, press material for 5 seconds

 PEEL Peel warm, cover with silicone sheet and re-press for 10 seconds

 Machine wash using mild detergent. Do not use bleach. Dry at a normal dryer setting on household machines. Do not iron directly onto this material. Wash temperature should not exceed 140°F.

METALLIC

- Old Gold TFT-14920★
- Bright Gold TFT-14921★
- Rose Gold TFT-14922★
- Bright Copper TFT-14924★
- Antique Silver TFT-14930★
- Bright Silver TFT-14931★



Check out our videos featuring this product, as well as many others. Subscribe to us on YouTube! [Youtube.com/SpecialtyMaterials](https://www.youtube.com/SpecialtyMaterials)

Test on dazzle cloth and other moisture-wicking polyesters. Moisture-wicking materials have better adhesion when washed and dried using no fabric softener or blotted with rubbing alcohol before pressing. Be advised that dye migration has occurred with low energy dyes in polyester and poly-blend fabrics.